

36" ELECTRIC RESTAURANT RANGE

4 French Plates / 12" Hot Top



Model EV36-S-4FP-1HT-208 shown with optional casters



SPECIFICATIONS

36" wide electric restaurant range, Vulcan Model No. EV36-S-4FP-1HT-208. Fully MIG welded aluminized steel frame for added durability. Stainless steel front, sides, backriser, plate shelf and 6" adjustable legs. Four 91/2" round French plates, 2 KW input per plate. Full width pull out crumb tray located beneath the cooking top. 12" wide, 24" long, Hot Top section. Comes with one standard oversized oven. Oven interior measures 26.5"w x 26.375"d x 14"h. Comes with one oven rack and three rack positions. Oven door is heavy duty with an integrated door hinge / spring mechanism, requiring no adjustments. 5 KW input. Top browning heat control. Thermostat adjusts from 200°F to 500°F. Oven controls are protected from heat in an insulated side compartment. Requires 208, 240, or 480 volt, 1 or 3 phase power supply. All ranges shipped in 3 phase and are field convertible to single phase.

Exterior Dimensions:

34% "d x 36" w x 58" h on 6" adjustable legs

Project		
AIA #	SIS #	
Item #	Quantity	C.S.I. Section 114000

MODELS

□ EV36-S-4FP-1HT-208	4 French Plates / One 12" Hot Top Standard Oversized Oven / 208V
□ EV36-S-4FP-1HT-240	4 French Plates / One 12" Griddle Standard Oversized Oven / 240V
□ EV36-S-4FP-1HT-480	4 French Plates / One 12" Hot Top Standard Oversized Oven / 480V

STANDARD FEATURES

- Fully MIG welded aluminized steel frame for added durability
- Stainless steel front, sides, back riser, shelf and legs
- Four 9½" round, 2 KW French plates with infinite heat control switches
- Full width pull out crumb tray
- One 12" x 24" thermostatically controlled hot top section
- 5 kW oven with top browning control
- Thermostat adjusts from 200°F to 500°F
- Cool-to-the-touch control knobs and oven handle
- One oven rack and three rack positions
- 18" x 26" sheet pans fit side to side and front to back
- Requires 208, 240 or 480 volt, 1 or 3 phase power supply. (Ranges shipped in 3 phase and are field convertible to single phase)
- One year limited parts and labor warranty

ACCESSORIES (Packaged & Sold Separately)

- Extra oven rack with two rack guides
- Set of four casters (two locking)
- \Box 10" stainless steel stub back
- 🗅 ESB36 salamander broiler
- □ Reinforced high shelf for ESB36 salamander broiler

Approved by_

Date

.

Date

Approved by



36" ELECTRIC RESTAURANT RANGE 4 French Plates / 12" Hot Top

INSTALLATION INSTRUCTIONS

Clearances from Combustible Construction	<u>Rear</u>	<u>Sides</u>
Range with Hot Top	0"	6"
Range with Griddle Top	0"	3"
Range with Griddle Top	0"	3"

Ranges with an ESB Salamander Broiler mounted above: Refer to the ESB Salamander Broiler spec sheet for clearance specifications.



AVAILABLE VOLTAGES - 208, 240 OR 408 VOLT - 1 OR 3 PHASE																
3 PHASE LOADING						NOMINAL AMPS PER LINE WIRE										
MODEL				3 PHASE									1 PHASE			
	CONNECTING			208 VOLT			240 VOLT		480 VOLT							
	KW	Х-Ү	Y-Z	x-z	х	Y	z	х	Y	z	х	Y	z	208V	240V	480V
EV36-S-4FP-1HT-208	18.0	5.0	8.0	5.0	41.6	54.1	54.1							86.5		
EV36-S-4FP-1HT-240	18.0	5.0	8.0	5.0				36.1	46.9	46.9					75.0	
EV36-S-4FP-1HT-480	18.0	5.0	8.0	5.0							18.05	23.45	23.45			37.5

This appliance is manufactured for commercial use only and is not intended for home use.

As continued product improvement is a policy of Vulcan, specifications are subject to change without notice.