VULCAN

48" ELECTRIC RESTAURANT RANGE 4 FRENCH PLATES / 24" GRIDDLE

Item #



Model EV48S-4FP24G208 shown with adjustable legs





SPECIFICATIONS

48" wide electric restaurant range, Vulcan Model No. EV48S-4FP24G208. Fully MIG welded aluminized steel frame for added durability. Stainless steel front, sides, back riser, plate shelf and 6" adjustable legs. Four 91/2" round French plates, 2 KW input per plate. Full width pull out stainless steel crumb tray located beneath the cooking top. 24" wide, 7/8" thick griddle plate, one thermostat provided for every 12" griddle width. Comes with one standard oversized oven. Oven interior measures 26½ "w x 263/8" d x 14"h. Comes with one oven rack and three rack positions. Oven door is heavy duty with an integrated door hinge / spring mechanism, requiring no adjustments. 5 KW input. Top browning heat control. Thermostat adjusts from 200°F to 500°F. Oven controls are protected from heat in an insulated side compartment. Requires 208, 240 or 480 volt, 1 or 3 phase power supply. All ranges shipped in 3 phase and are field convertible to single phase.

Exterior Dimensions:

34"d x 48"w x 58"h on 6" adjustable legs

□ EV48S-4FP24G208 4 French Plates / 24" Griddle / Standard Oversized Oven / 208V

□ EV48S-4FP24G240 4 French Plates / 24" Griddle / Standard Oversized Oven / 240V

□ EV48S-4FP24G480 4 French Plates / 24" Griddle / Standard Oversized Oven / 480V

STANDARD FEATURES

- Fully MIG welded aluminized steel frame for added durability
- Stainless steel front, sides, back riser, shelf and legs
- Four 9½" round, 2 KW French plates with infinite heat control switches. Four position heat switch on 480 volt.
- 5 KW oven with top browning control
- One standard oversized oven, interior measures 26½ w x 26¾ d x 14 h
- Full width pull out stainless steel crumb tray
- 24" wide, 7/8" thick griddle plate, one thermostat provided for every 12" griddle width
- Thermostat adjusts from 200°F to 500°F
- Cool to the touch control knobs
- One oven rack and three rack positions
- 18" x 26" sheet pans fit side to side and front to back
- Requires 208, 240 or 408 volt, 1 or 3 phase power supply. (Ranges shipped in 3 phase and are field convertible to single phase)
- One year limited parts and labor warranty

| ACCESSORIES (| Packaged & | Sold So | eparately | /) |
|----------------------|------------|---------|-----------|----|
|----------------------|------------|---------|-----------|----|

□ Extra oven rack with two rack guides
 □ Set of four casters (two locking)
 □ 10" stainless steel stub back
 □ ESB36 salamander broiler
 □ Reinforced high shelf for ESB36 salamander broiler
 □ Towel bar
 □ Cutting board
 □ Condiment rail
 □ Fryer shield



P.O. Box 696 Louisville, KY 40201 Toll-free: 1-800-814-2028 Local: 502-778-2791 Quote & Order Fax: 1-800-444-0602





48" ELECTRIC RESTAURANT RANGE 4 FRENCH PLATES / 24" GRIDDLE

INSTALLATION INSTRUCTIONS

| Clearances from Combustible Construction | Rear | <u>Sides</u> |
|--|------|--------------|
| Range with French Plates | 0" | 3" |
| Range with Griddle Tops | 0" | 3" |
| Range with Hot Tops | 0" | 6" |

Ranges with an ESB Salamander Broiler mounted above: Refer to the ESB Salamander Broiler spec sheet for clearance specifications.





The EV 48 ranges require two separate electrical hook-ups.

| | | | | AVA | ILAE | LE V | OLTA | GES | - 208 | OR | 240 \ | OLT | - 1 0 | R 3 F | PHAS | E | | | | | | | | | |
|-----------------|-----|------|--------------|-----|------|----------------------------|------|------------|----------|------|-------|----------|------------|-------|----------|------|------|----------|---------|------|------|------|------|------|--|
| 3 PHASE LOADING | | | | | | NOMINAL AMPS PER LINE WIRE | | | | | | | | | | | | | | | | | | | |
| MODEL NUMBER | le! | \A/ | kW PER PHASE | | | | | 3 PHASE LT | | | | | 3 PHASE RT | | | | | | 1 PHASE | | | | | | |
| | K | W | LT 3 PH | | | RT 3 PH | | | 208 VOLT | | | 240 VOLT | | | 208 VOLT | | | 240 VOLT | | | LT | | R | RT | |
| | LT | RT | X-Y | Y-Z | X-Z | X-Y | Y-Z | X-Z | Х | Υ | Z | Х | Υ | Z | Х | Υ | Z | Х | Υ | Z | 208 | 240 | 208 | 240 | |
| EV48S-4FP24G208 | 4.0 | 15.8 | 2.0 | 2.0 | 0.0 | 3.4 | 7.4 | 5.0 | 8.3 | 16.7 | 8.3 | | | | 35.0 | 45.0 | 51.6 | | | | 20.3 | | 76.0 | | |
| EV48S-4FP24G240 | 4.0 | 15.8 | 2.0 | 2.0 | 0.0 | 3.4 | 7.4 | 5.0 | | | | 7.3 | 14.5 | 7.3 | | | | 30.3 | 39.0 | 44.7 | | 16.7 | | 65.8 | |

Note: To calculate 480 volt amps, take 240 volt amp ratings shown and divide by two.

This appliance is manufactured for commercial use only and is not intended for home use.



a division of ITW Food Equipment Group LLC

P.O. Box 696 ■ Louisville, KY 40201 ■ Toll-free: 1-800-814-2028 ■ Local: 502-778-2791 ■ Quote & Order Fax: 1-800-444-0602

